

# System Parameters

04 May 2024





TM and copyright © 2010-2024 Imagicle spa

# Table of Contents

System Parameters	
Outgoing Email Shared Parameters	
Microsoft OAuth2 Authentication for email sending	
Numbering Plan	
Users Authentication Settings	
Proxy settings	
Imagicle Cloud services authentication data	
Web Server setting	

# **System Parameters**

## **Outgoing Email Shared Parameters**

Common email parameters enable Imagicle UCX On-prem/Cloud Suite to send email notifications through your company email server. Imagicle UCX Suite leverages this feature to forward voicemail messages, incoming faxes, scheduled reports, alarms, and to notify to the administrators about applications events.

This section describes those settings and their meaning. You can change them by clicking the **System parameters** link in the **Admin** menu, then pressing the **Outgoing Email Parameters** button.

## **SMTP** Configuration

Typically, on-prem email servers like MS-Exchange or Lotus Domino leverage this protocol. In this case, you can select "SMTP" from **Protocol Type** pull-down menu. Please fill the resulting form based on your own email system:

Imagicle UCX Suite	<b>Ø</b>		<b>19</b> 3	D£	Ų			(
Administration	User Manag	gement S	ystem Para	meters Lic	enses Suppo	ort Monito	oring Pres	ence
« Back								
Outgoing Email Par	ameters							
Enable Outgoing Mail								
Protocol Type		SMTP				$\overline{}$		
Email From Address		fax-ha@	⊉imagiclevç	g.lab				
Server Name		192.16	8.4.6					
Server Port		25						
Use Authentication		✓						
Username		fax-adn	nin@imagio	levg.lab				
Password		•••••	••					
Proxy		NoProx	y			~		
		Change	proxy setti	ngs				
					Test conne	ction	Save	

- Enable Outgoing Mail: must be checked to enable Imagicle UCX Suite to send emails. **This is mandatory for fax-to-email feature**, if you are leveraging Imagicle Digital Fax application.
- Protocol Type: SMTP

- Email Form Address: This is the address which appears in the "From" field of the mail sent by UCX Suite. Depending on SMTP relay server, this might be a dummy address or an actual email account.
- Server Name: enter the FQDN or the IP address of the email server.
- Server Port: enter the port number on which the mail server is listening (example 25 for SMTP and 465/587 for Secure SMTP).
- Use authentication, Username, and Password: fill these fields if authentication is required.
- Proxy: If a Proxy is in place, please select it. More info here.

**Secure SMTP is also supported**. The protocol to be used is auto-detected from the remote server choosing the safest first: TLS (we do support 1.2 - 1.0) or SSL (3.0 - 1.0) or plain.

Press the "Test" button to test the connection. Remember to press the "Update" button to save the changes before leaving.

**Warning**: even if the connection test succeeds, some email server might reject the "email from" address at the moment the email message is sent. Please check your email server configuration.

## **OAuth2 Configuration**

If you are leveraging a Cloud-based email service, like Office365 or Google Mail, then likely you wish to enable email sending by leveraging OAuth2 modern authentication. In this case, you first need to create an App Registration (if not available yet), by following this <u>KB article</u>.

Then you need to create a DEDICATED email account in your Office365 Tenant, used by UCX Suite to populate the "From" field of the emails to be sent to users.

Please select "Office 365" from Protocol Type pull-down menu. Please fill the resulting form based on your own email system:



- Enable Outgoing Mail: must be checked to enable Imagicle UCX Suite to send emails. **This is mandatory for fax-to-email feature**, if you are leveraging Imagicle Digital Fax application.
- Protocol Type: Office 365
- Application (client) ID: This field must be populated based on App Registration
- Directory (tenant) ID: This field must be populated based on App Registration
- Client secret: This field must be populated based on App Registration
- Email Address: This is the dedicated email account created on purpose for email sending.
- Proxy: If a Proxy is in place, please select it. More info here.

### Companies leveraging a custom Office 365 URL

Some companies are leveraging a custom Office 365 URL to access their email service (like Office 365 Business service).

To change from default Office 365 URL to a custom URL, you must change two internal Windows system variables, by access Imagicle instance through a RDP session:

- IMAGICLE\_OUTGOING\_O365\_AUTHENTICATION\_URL
- (default: https://login.microsoftonline.com)
- IMAGICLE\_OUTGOING\_O365\_SERVER\_URL
  - ♦ (default: https://outlook.office365.com)

If you are leveraging an Imagicle UCX Cloud Suite, please contact Imagicle team to let them apply the change for you.

## Email queuing for high reliability

Imagicle UCX Suite integrates an email messaging queue which prevents losing notifications when the connection with the email server fails.

If Outgoing Email Parameters has never been configured (especially the server IP address), connection is not attempted, outgoing emails are not generated, voicemail messages and incoming faxes may never reach their recipients.

If Outgoing Email Parameters are wrong, or if the email server cannot be reached at the moment, email messages are generated and stored in a local folder ("StonevoiceAS\Var\Spool\Pickup"). As soon as the connection is available, all the messages stored in queue are sent.

The queue service tries to reconnect to the email server every 30 seconds. The email messages are sent one by one in sequence.

## Microsoft OAuth2 Authentication for email sending

This authentication method is supported by Imagicle UC Suite, starting from 2021.Winter.2 release, and it relays on advanced OAuth2 authentication available for cloud-based Office 365 email service. Previous Imagicle releases are supporting OAuth2 basic authentication, which is dismissed by Microsoft starting from July 2021.

### **Requirements**

In order to enable Imagicle UCX Suite to send email notifications and to handle email-to-fax service, leveraging Microsoft Office 365 cloud service and OAuth2 authentication, you must configure an application on <u>Azure Web Portal</u>, taking note of Application ID, Directory ID and Client Secret data, needed later on while configuring this authentication method on Imagicle UCX Suite. Please read the following procedure to create a new application on Azure portal.

### Azure web portal configurations

Please access to Azure portal and go to "App Registrations"

Microsoft Azure	𝒫 Search resources, services, and docs (G+/)
Home >	
App registrations 👒	
+ New registration 🔀 Endpoints 🔗 Troubl	leshooting 🞍 Download 💀 Preview features 🛛 🛇 Got feedback?
Try out the new App registrations search preview	w! Click to enable the preview. $ ightarrow$
<ul> <li>Starting June 30th, 2020 we will no longer add a to be upgraded to Microsoft Authentication Libr</li> <li>All applications</li> </ul>	iny new features to Azure Active Directory Authentication Library (ADAL) and Azure AD Graph. We will continue to provide techn rary (MSAL) and Microsoft Graph. Learn more
Start typing a name or Application ID to filter	these results
Display name	Application (client)
G GiulianoAppTest	3d62f992-8a29-4fd
TE TestAuthApp	2a321830-4133-4f6
CA CallBot	47e27225-b893-417
MY myMessagingBot	83a0bc9b-3c74-457
TE Test1	5025cb0b-e879-46c

Click on "New registration" and choose a name like "MyOAuth2App". Then select "Accounts in this organizational directory only" and hit "Register"

■ Microsoft Azure	℅ Search resources, services, and docs (G+/)
Home > App registrations >	
Register an application	
Name	
The user-facing display name for this application (thi	s can be changed later).
MyOAuth2App	×
Supported account types	
Who can use this application or access this API?	
Accounts in this organizational directory only (In	nagicle spa only - Single tenant)
O Accounts in any organizational directory (Any Az	zure AD directory - Multitenant)
O Accounts in any organizational directory (Any Az	zure AD directory - Multitenant) and personal Microsoft accounts (e.g. Skype, Xbox)
O Personal Microsoft accounts only	
Help me choose	
Redirect URI (optional)	
We'll return the authentication response to this URI a changed later, but a value is required for most authe	fter successfully authenticating the user. Providing this now is optional and it can be ntication scenarios.
Public client/native (mobile 🗸 e.g. myapp:,	//auth 🗸
By proceeding, you agree to the Microsoft Platform F	Policies 🗗

Register

The following window appears, including Application ID and Directory ID. Please copy both data, for later usage.

Microsoft Azure	
Home > App registrations > MyOAuth2App ☆	
	💼 Delete 🌐 Endpoints 💀 Preview features
. Overview	↑ Essentials
📣 Quickstart	Display name : MyOAuth2App
🚀 Integration assistant	Application (client) ID : 1cb8b5d2-8724-4f32-8152-a16a230b682b
	Directory (tenant) ID : 969d5b92-bc05-403f-b576-97201b665e65
Manage	Object ID : 2c6bb16d-26b0-4910-8f6a-cff87b64bb2e
💳 Branding	
Authentication	Welcome to the new and improved App registrations. Looking to learn how it's changed from App registrations (Legac
📍 Certificates & secrets	
Token configuration	Starting June 30th, 2020 we will no longer add any new features to Azure Active Directory Authentication Library (ADA longer provide feature updates. Applications will need to be upgraded to Microsoft Authentication Library (MSAL) and
<ul> <li>API permissions</li> </ul>	

Now please click on "Certificates & secrets" option, included in left pane, and add a new "client secret" with the name of your choice and a long expiration period.

■ Microsoft Azure	
Home > App registrations > MyOAut	h2App
🔶 MyOAuth2App   Ce	ertificates & secrets 👒
Search (Ctrl+/) «	♡ Got feedback?
Overview	Add a client secret
🗳 Quickstart	Description
🚀 Integration assistant	DigitalFaxMailServiceSecret
Manage	Expires
🔤 Branding	In 2 years
Authentication	
📍 Certificates & secrets	
Token configuration	Add Cancel
<ul> <li>API permissions</li> </ul>	
Expose an API	Client secrets
App roles   Preview	A secret string that the application uses to prove its identity when requesting a tok
B Owners	
Roles and administrators   Preview	+ New client secret
Manifest	Description Expires Value
Support + Troubleshooting	No client secrets have been created for this application.

Once added, you'll get some data associated to it. Please copy "Value" field for later usage. Copy the field immediately after having created the client secret, because it will be automatically hidden after few minutes, for security reasons.

	Microsoft Azure		es, and docs (G+/)		
Hon	ne > App registrations > MyOAu	th2App			
•	MyOAuth2App   C	ertificates & secrets	\$		
٩	Search (Ctrl+/) «	♡ Got feedback?			
15	Overview	Copy the new client secret value	e. You won't be able to retrieve it a	after you perform another	operation or leave this blade.
<b>4</b> 2	Quickstart	,·	,		
*	Integration assistant				
Man	age	Certificates			
	Branding	Certificates can be used as secrets to	prove the application's identity	y when requesting a tok	en. Also can be referred to as
Э	Authentication	Upload cortificato			
•	Certificates & secrets	opioad certificate			
11	Token configuration	Thumbprint		Start date	Expires
÷	API permissions	No certificates have been added for	this application.		
۵	Expose an API				
24	App roles   Preview				
4	Owners	Client secrets			
	Roles and administrators   Preview	A secret string that the application u	ses to prove its identity when re	equesting a token. Also	can be referred to as application
0	Manifest	+ New client secret		_	
Sup	port + Troubleshooting	Description	Expires	Value	
B	Troubleshooting	DigitalFaxMailServiceSecret	12/31/2299	uJO9k3_x03-d-7cF	~TptM9YDAEV84QJNv6

Now click on "Add permissions" and select "API's my organization users". Then search for "Office 365 Exchange online".

p	Request API permissions	
ermissions 🖈		
◯ Refresh 🛛 ♡ Got feedback?	Select an API           Microsoft APIs         APIs my organization uses         My APIs	
onfigured permissions	Apps in your directory that expose APIs are shown below	
pplications are authorized to call APIs when they are granted permission I the permissions the application needs. Learn more about permission	ons by us s and cor	
ria de Serve de la	Name	Application (client)
+ Add a permission 🗸 Grant admin consent for Imagicle spa	Office 365 Enterprise Insights	f9d02341-e7aa-4560
API / Permissions name Type Description	Office 365 Exchange Online	0000002-0000-0ff1
✓ Microsoft Graph (1)	Office 365 Information Protection	2f3f02c9-5679-4a5c
User.Read Delegated Sign in and rea	d user pr Office 365 Management APIs	c5393580-f805-4401
	Office 365 Search Service	66a88757-258c-4c72
> view and manage permissions and user consent, try Enterprise applic	ations. Office 365 SharePoint Online	0000003-0000-0ff1

Select "Office 365 Exhange online" and then select "Application Permissions"

Request API permissions		×
<ul> <li>All APIS</li> <li>Office 365 Exchange Online https://outlook-tdf-2.office.com/</li> <li>What type of permissions does your application require?</li> </ul>		
Delegated permissions Your application needs to access the API as the signed-in user.	Application permissions Your application runs as a background service or daemon without a signed-in user.	а
	Your application runs as a background service or daemon without a signe	d-in user.

#### From the list of available permission levels, please select "full\_access\_as\_app" from "Other permissions" category.

	PS	earch resources, services, and docs (G+/)			Σ	Q (	2	?	٢	aldo.antignar
PoigitalFax Fax   API permissions	Â			Request API permissions						
🖒 Refresh 🛛 🛇 Got feedback?				C All APIs Office 365 Exchange Online https://outlook-tdf-2.office.com/						
onfigured permissions				What type of permissions does your application require?						
pplications are authorized to call APIs whe I the permissions the application needs. Le	n they are garn more a	granted permissions by users/admins as pa bout permissions and consent	rt of the consent process. The list of co	Delegated permissions Your application needs to access the $\ensuremath{API}$ as the signed-in user.		Application Your applic signed-in u	ation runs a ser.	ins as a baci	kground s	service or daemo
<ul> <li>Add a permission</li> <li>Grant admin of</li> </ul>	onsent for	inagicie spa								
API / Permissions name T	ype	Description	Admin consent req	Select permissions						
✓ Microsoft Graph (1)				P Start typing a reply url to filter these results						
User.Read D	elegated	Sign in and read user profile		Permission				Ad	lmin con	isent required
> view and manage permissions and user o	consent, try	Enterprise applications.		✓ Other permissions (1)						
				full_access_as_app ①           Use Exchange Web Services with full access to all mailbox	oxes			Ye	s	
				> Calendars						
				Contacte						

Once permission has been assigned, you must authorize it for your organization, by clicking on "Grant admin consent for <company\_name>".

	0	Search recourses sensines and done (G+A			
	7	Search resources, services, and docs (G+/)			_
ail2DigitalFax					
alFax   API permission	ns 🖈				
🕐 Refresh 🛛 🛇 Got feedback	3				
A You are editing permission(s) to	o your application, u	users will have to consent even if they've already done so previou	isly.		
Configured permissions					
Applications are authorized to call A all the permissions the application n	Pis when they are needs. Learn more	granted permissions by users/admins as part of the conser about permissions and consent	nt process. The list of con	figured permissions should inc	lude
+ Add a permission 🗸 Grant	admin consent fo	or Imagicle spa			
API / Permissions name	Туре	Description	Admin consent req	Status	
✓ Microsoft Graph (1)					
User.Read	Delegated	Sign in and read user profile	-		
✓ Office 365 Exchange Online	(1)				
full access as app	Application	Use Exchange Web Services with full access to all mailb	Yes	A Not granted for Imagicl	
nis is the resulting page.					8
Search resources, services	s, and docs (G+/)				Ę
ssions 🖈					
🕐 Refresh 🛛 🛇 Got feedback?					
onfigured permissions					
pplications are authorized to call AP II the permissions the application ne	eds. Learn more a	granted permissions by users/admins as part of the consen about permissions and consent	t process. The list of con	figured permissions should inc	lude
🕂 Add a permission 🗸 Grant a	dmin consent for	Imagicle spa			
API / Permissions name	Туре	Description	Admin consent req	Status	
✓ Microsoft Graph (1)					
User.Read	Delegated	Sign in and read user profile	2	🥝 Granted for Imagicle spa	
✓ Office 365 Exchange Online (1	)				
full access as ann	Application	Use Exchange Web Services with full access to all mailb.	Ves	Granted for Imagicle spa	

To view and manage permissions and user consent, try Enterprise applications.

### Optional configurations to restrict EWS Application to a mailbox set (Imagicle Digital Fax only)

Above described API Permission level privileges allows the application to access all EWS API on all organization mailboxes.

However, it's possible to optionally apply an advanced configuration on Microsoft Office 365 to restrict the application to access only a specific mailbox.

This is accomplished by accessing Exchange Online Administration Portal and create a new mail-enabled security group: Go to **Recipients** â **Groups** â **New mail-enabled security group** 



Fill the form with a name and an alias. Those will be used later as a target of an Application Policy.

New Mail-enabled security group - Lavoro - I	Vicrosoft Edge	- 0	×
https://outlook.office365.com/	ecp/UsersGrou	ps/NewSecu	rity
new mail-enabled security grou	p		
Mail-enabled security groups can be used to distribute messages and to assign access permissions to Active Directory resources. Le more	arn		Å
Imagicle Digital Fax			- 1
*Alias:			- 1
imagicle.digital.fax			- 1
*Email address:			- 1
imagicle.digital.fax @ imagicleucdev.onr	micro 🗸		
Notes:			
*Owners:			
+ -			-
	Save	Cancel	

Save form and edit the newly created group, go to **membership**, add a member, search for the mailbox to be granted to Digital Fax and add it:

端 Edit Mail-enabled security group - Lavoro - Microsoft Edge

#### https://outlook.office365.com/ecp/UsersGroups/EditSecurityDistributionGroup.aspx?Activ ( )

Imagicle Digital Fax

0	on	0	col.	
ч			a	
-				

### membership

general M ownership	embers:							
membership approval	🍇 Select Members - Lavoro - M	icrosoft Edge — 🗆	×					
delivery management	https://outlook.office365.com/ecp/Pickers/MemberPi     P S ···							
message approval email options								
MailTip	DISPLAY NAME	EMAIL ADDRESS						
group delegation	Adele Vance Alex Wilber Diego Siciliani	AdeleV@imagicleucdev.onmicrosoft.com AlexW@imagicleucdev.onmicrosoft.com DiegoS@imagicleucdev.onmicrosoft.com	*					
	Digital Fax	fax@imagicleuci/ev.onmicrosoft.com						
	Grady Archie	GradyA@imagicleucdev.onmicrosoft.com						
	Henrietta Mueller	HenriettaM@imagicleucdev.onmicrosoft						
	Imagicle Digital Fax	imagicle.digital.fax@imagicleucdev.onmic						
	Isaiah Langer	lsaiahL@imagicleucdev.onmicrosoft.com						
	Johanna Lorenz	JohannaL@imagicleucdev.onmicrosoft.com						
	Joni Sherman	JoniS@imagicleucdev.onmicrosoft.com						
	Lee Gu	LeeG@imagicleucdev.onmicrosoft.com						
ttps://outlook.office365.com/ecp/Use	Lidia Holloway	LidiaH@imagicleucdev.onmicrosoft.com						
	1 selected of 20 total							
	add -> Digita	al Fax[remove];						
		OK Cancel						

Connect to Exchange Online PowerShell and create an Application Access Policy to allow Digital Fax application to only access the newly created mail security group, by executing the following command, where:

• Appld value corresponds to the application "Client ID" value created within Azure app registration portal

• PolicySecurityGroupId corresponds to "Display Name" of the previously create security group

New-ApplicationAccessPolicy -AccessRight RestrictAccess -AppId <AppId> -PolicyScopeGroupId "Imagicle Digital Fax" -D

#### Output should be:

```
RunspaceId : 2d08b315-81dd-4140-8a28-4a49431fb44d
ScopeName : Imagicle Digital Fax
ScopeIdentity : Imagicle Digital Fax
Identity
8f8ccdec-23bd-4452-bdb3-becc0c415a99\da34af4b-b01f-47e4-bfac-2f9fc3f1383e:S-1-5-21-2724517575-989
                : da34aq4b-b01f-47e4-bfac-2f9fc3f1383e
AppId
ScopeIdentityRaw :
S-1-5-21-2724537575-989916663-4003715733-16076635;697c48d2-f812-4072-a10f-4455db66025e
Description : Restrict Imagicle Digital Fax accessible mailboxes
                : RestrictAccess
AccessRight
ShardType
               : All
               : True
IsValid
ObjectState : Unchanged
```

#### Verify the rule, to check if the application can properly access the needed mailbox by executing the following command:

Test-ApplicationAccessPolicy -Identity <mail2fax address> -AppId <clientId>

#### Output should be:

```
RunspaceId : 2e08b315-81dd-4143-8a28-4a49431fa44d AppId :
da34ee4b-b01f-44e4-bfac-2f9fc3f1383e Mailbox : fax MailboxId :
c82eee91-a3e0-43f0-9a43-03e7ec7b1e96 MailboxSid :
S-1-5-21-2722357575-989916663-4003711733-159675946 AccessCheckResult : Granted
```

#### Then please verify the application can't access any other mailbox, by executing the following command:

Test-ApplicationAccessPolicy -Identity <any other mail address> -AppId <clientId>

#### In this case, output should be similar to below sample:

```
RunspaceId : 2d08b235-81dd-4140-8a28-4a49431fa44dAppId :
da34af4e-b01f-47e4-beec-2f9fc3f1383eMailbox : faxMailboxId :
c82eee91-a3e0-43f0-9a43-03c7ec7b1e96MailboxSid :
S-1-5-21-272451125-989916663-4003715733-15450946AccessCheckResult : Denied
```

## **Numbering Plan**

You can edit these parameters through the **Admin** -> **System parameters** link in the App Suite menu, pressing the **Numbering Plan Parameters** button. These settings apply to the applications that make and receive calls such as Attendant Console and Speedy. To be able to modify a parameter, you have to deselect "Use default settings".

## General

General settings affect both incoming and outgoing calls.

- Internal Phone Number Patterns: These patterns identify the internal PBX extensions and, in general, all numbers that do not require the PSTN access code to be dialled. The usual range is 1 5. The list of patterns is checked top-down. To know how to build the pattern, please refer to the online help in the web page.
- PBX supports E.164 dialling: flag this checkbox if you use the + to dial external numbers (e.g. +123456789)
- Local Country Code: This prefix will be stripped from the caller number before looking for it in Speedy directories (e.g. +44). Incoming prefix will be stripped first, then the Local country code. You can specify only one prefix.
- International Dialling Prefix: This is the prefix needed to reach international numbers when the + sign is not used. E.g. 00 in European countries, +1 in US.

### **Incoming calls**

• **Prefix** for incoming calls: This prefix will be stripped from the caller number before looking for it in Speedy directories. Example: if your outgoing prefix is 0, it is likely that the PBX adds 0 to the caller number to allow redialling. In this case enter 0 as incoming prefix.

### **Outgoing calls**

- **Prefix** for outgoing calls: This prefix will be automatically added to outgoing calls, e.g. to calls placed by Speedy towards external numbers. This prefix won't be added to internal calls nor to calls towards the users' primary extension configured in the users list
- Suffix for outgoing calls: On some telephony systems, a suffix can be used to quicken the destination selection (for instance #)
- **TAPI events include the prefix**: set this flag to on if the called number which the pbx signals through TAPI calls includes the prefix for outgoing calls, so that it will be stripped. This should happen only if the outgoing prefix is removed by a voice gateway instead of the PBX. This setting affects the lookup in Speedy directories for the **called** numbers of outgoing calls.

## **Users Authentication Settings**

This important setting dictates the authority in charge of authenticate users upon accessing Imagicle web portal, gadgets and Attendant Console. Within same page, you can also setup the https session expiration timeout for Imagicle web portal and gadgets.

This setting is available from Imagicle UCX Suite web portal: Admin â System Parameters â Users authentication settings.

## Users authentication preferences

D > AD/LDAP > Local D > AD/LDAP > Local D > Cisco UCM > Local O > Local O > AD/LDAP > Cisco UCM > Local O > Cisco UCM > AD/LDAP > Local	redentials of the external IdP. If S will log in using those credentials	SO is not enabled, user . All other users should	's configured with provide their local
settings to keep the user's web session	active. Please, notice that this feature	e works only for HTTPS	protocol.
· ·			
day(s)			
		Save	Cancel
	> AD/LDAP > Local > AD/LDAP > Local > Cisco UCM > Local > Local > AD/LDAP > Cisco UCM > Local > AD/LDAP > Cisco UCM > Local > Cisco UCM > AD/LDAP > Local settings to keep the user's web session v day(s) ()	> AD/LDAP > Local > AD/LDAP > Local > Cisco UCM > Local > Local > AD/LDAP > Cisco UCM > Local > AD/LDAP > Cisco UCM > Local > Cisco UCM > AD/LDAP > Local settings to keep the user's web session active. Please, notice that this feature aday(s) 3	> AD/LDAP > Local > AD/LDAP > Local > Cisco UCM > Local > AD/LDAP > Cisco UCM > Local > AD/LDAP > Cisco UCM > Local > AD/LDAP > Cisco UCM > Local > Cisco UCM > AD/LDAP > Local Settings to keep the user's web session active. Please, notice that this feature works only for HTTPS day(s) (1)

As you can see in above screenshot sample, it includes several different authentication authorities. Please configure the one corresponding to your synchronization source:

- SSO > AD/LDAP > Local: Choose this option when you import users from Active Directory, from Azure AD, from a generic LDAP server or from Imagicle LDAP Module.
- SSO > Cisco UCM > Local: Choose this option while importing users from Cisco UCM (via AXL) or from Cisco Webex Control Hub.
- SSO > Local: This is the local authentication, leveraging a local username and password assigned to each Imagicle user and stored into Imagicle SQL Server instance.
- SSO > AD/LDAP > Cisco UCM > Local: Choose this option to authenticate users against Active Directory or generic LDAP. If AD/LDAP username is missing and PBX Username is configured, users are authenticated against Cisco UCM.
- SSO > Cisco UCM > AD/LDAP > Local: Choose this option to authenticate users against Cisco UCM. If PBX Username is missing and AD/LDAP username is configured, users are authenticated against Active Directory or generic LDAP.

Please note that all above options include <u>SSO authentication</u> against a configured Identity Provider. If SSO is not used, and relevant User's field is left empty, then authentication is skip to next listed option.

All above choices include "Local" as last authentication option, meaning UCX Suite authentication leveraging a local username and password assigned to each Imagicle user and stored into Imagicle SQL Server instance.

### User session management

This setting allows to enable a persistent active web session for users leveraging Imagicle web portal and/or Imagicle gadgets.

If this feature is enabled, by configuring "Remember logged in user" to Yes, users can shut down own workstations or close the web browser without loosing entered login credentials. Next time they access to Imagicle web portal or gadget within configured inactivity period, they are redirected to web portal's home page or gadgets' main pages.

The feature is enabled by default, with an inactivity timeout of 8 days. You an increase this parameter up to 30 days.

## **Proxy settings**

This article is applicable to Imagicle UC Suite 2019. Summer. 1 or later and it allows to apply a Proxy configuration to reach Internet addresses, specifically for the following features:

- Imagicle Online License Activation, where you need to reach Imagicle Cloud services at https://\*.imagicle.com
- Imagicle Cloud Services Authentication
- Cloud-based email services, like Office365 or Google mail
- Imagicle Webex connector for users' synchronization
- Microsoft Teams phone control and presence Cloud services (2021.Summer.1 and above)

You can edit these parameters through the Admin â System parameters link in the App Suite menu, hitting "Proxy settings" button.

System parameters	
IP Telephony system parameters	Set »
SMTP parameters	Set »
Numbering plan parameters	Set »
Users authentication settings	Set »
Proxy settings	Set »
Secure communications certificate	Set »
Imagicle Cloud services authentication data	Set »

## Proxy

You can either enable a HTTP/HTTPS-based proxy server and/or a SOCKS v4/v5 proxy server. In both cases, these are the field to be compiled:

- Address: this is the proxy URL or IP address. This parameter is mandatory
- Port: This is the TCP port used by proxy. If above address is entered, port is mandatory
- Username: the username for proxy authentication (if needed). Currently, username can't include "@" character.
- **Password**: the password for proxy authentication. If above username is entered, password is **mandatory**. Currently, password can't include "@" character.

Proxy			
If this machine r described at the	needs proxies to reach external resources, yo following link: https://www.imagicle.com/go,	u can set them /IASProxy	here. Please make sure the proxy configurations complies with the requirements
HTTP/HTTPS			
Address	10.0.0.2	Port	3128
Username	httpUsername		
Password	•••••		
SOCKS			
Address	10.0.0.4	Port	3129
	●SOCKS v4		
Username	SOCKSUsername		
Password	•••••		
			Save

Configuring a proxy directly on the UC Suite server network settings is discouraged. If needed for specific requirements (e.g. allow SO Updates), below options are available:

- enable it temporarily and then disable it when it is not longer necessary
- enable it and allow all direct communications between UC Suite and all other Imagicle cluster nodes (in case of HA installation), the PBX and all other 3rd party elements (e.g. AD/LDAP sources)

In case of HA installation, proxy configuration is not replicated among Imagicle cluster nodes.

**Warning:** The UC Suite should obtain api.imagicle.com SSL certificate and not the proxy certificate, otherwise security check fails. The proxy works in transparent way, so it should not perform https "decrypt & scan".

Warning: Every time you apply a new proxy configuration, please reboot Imagicle UC Suite server to enable it.

## Imagicle Cloud services authentication data

## Applies to

Imagicle UC Suite 2022.Winter.1 and above.

## Description

Several Imagicle Cloud-based services require to enable communication and data exchange between UC Suite and Imagicle Cloud. This is accomplished by entering authentication parameters, as below explained.

### **Requirements**

Please make sure you have the following data upfront:

- Customer name
- License activation token of Cloud-connected Imagicle UC Suite or Imagicle UC Cloud Suite

Please send above data to Imagicle Support Team.

Once the authentication is enabled on Imagicle side, Support Team returns you via email a "Client ID" and a "Client Secret" strings, to be applied by following below procedure.

## Solution

Please access Imagicle UC Suite web portal as administrator and go to ADMIN â System Parameters â Imagicle Cloud services authentication data

Fill both Client ID and Client secret fields with OAuth2 authentication data provided by Imagicle Cloud Services and hit Save. See below screenshot sample:

Imagicle UC Suite	÷.	2		B£	Ų	۵		\$	•			
Administration	User Manag	ement S	ystem Parar	meters Lice	nses Supp	ort Monito	oring Pres	ence Jabb	er High A	vailability	Audit Trail	
« Back												
Imagicle Cloud set	rvices auther	ntication	data									
Here you can enter t	the data requi	red to auti	h <mark>enticate t</mark> h	is UC Suite	to Imagicle	Cloud servi	ices. This c	lata is provi	ded by the	Imagicle C	Cloud platfo	rm.
To set up communication the data in memory	ation and data and keep all f	exchange ields empt	e between U :y.	IC Suite and	Imagicle C	oud, fill in	all fields w	ith valid dat	ta; in case	no connect	tion is expe	cted, remove
Client ID		clientId										
Client secret		•••••	•••••									
												Save

Credentials are encrypted and locally stored. The following window appears:



If, in the future, a credentials change is required, you can hit "Forget" button to remove existing credentials and enter new ones.

If your company is leveraging a Proxy server to provide Internet access, you should enter relevant parameters, as described in <u>this</u> article.

### **UC Suite cluster**

In High Availability environments or UC Cloud Suite implementation, above configurations must be performed in each node of the cluster, since the data are not duplicated and are not managed by the Backup/Restore procedure.

Each node just uploads its own recordings.

### Troubleshooting

If an error occurs upon loading the OAuth2 credentials, you can retry credentials saving. More error details can be found in the following log file:

C:\Program Files (x86)\StonevoiceAS\Var\Log\w3wp\**ApplicationSuite.log** 

## Web Server setting

This article is applicable to Imagicle UCX Suite 2023. Spring. 1 or later and it allows to change the embedded web server's URL to reach Imagicle web portal and leverage Imagicle APIs.

### How to change web server's URL

Please click on "Set  $\hat{A}$ »" beside "Web server settings" menu option. See below:

System parameters	
IP Telephony system parameters	Set »
SMTP parameters	Set »
Numbering plan parameters	Set »
Users authentication settings	Set »
Proxy settings	Set »
Secure communications certificate	Set »
Imagicle Cloud services authentication data	Set »
Web server settings	Set »

#### The following window pops-up:

Web server settings		
Enter your custom UCX Suite ba https:// <servercomputername></servercomputername>	ase URL here to make this UCX Suite node reachable. If no base URL has been specified, the default > URL will be used.	
Please note that this configurati according to the needs of your	on is valid on this node. If your environment consists of multiple nodes, be sure to configure the URL on network.	each of them
UCX Suite base URL		
	To save your base URL, please enter it in this order: < https://example.com/ >	
		Save

Here you can enter the URL of your choice, keeping in mind that https usage means involving a Digital Certificate which should be associated to the new URL within IIS. New URL <u>overrides</u> the existing https://<ServerComputerName> standard FQDN.

Once new URL is entered and saved, this is the result:

#### Web server settings

Enter your custom UCX Suite base URL here to make this UCX Suite node reachable. If no base URL has been specified, the default https://<servercomputername> URL will be used.

Please note that this configuration is valid on this node. If your environment consists of multiple nodes, be sure to configure the URL on each of them according to the needs of your network.

UCX Suite base URL: https://test.imagicle.com

Forget

"Forget" button allows to revert to standard FQDN. New web server URL is saved in: C:\Program Files (x86)\Apps\ApplicationSuite\Settings\**ApplicationSuite.Local.ini**